

Auto Fusion™ Static-Mix Airless Spray Gun

The Static Mix Auto Fusion™ gun guarantees the best mix on the market. Two mixer housings are available depending upon your flow requirements.

FEATURES

- Standard or high-flow static mix housings are available
- Adaptor supplied to use standard spray tips
- Solvent flush port provided to clean static mixers
- Optional heated manifold maintains consistent viscosity at the mix head

OPTIONS

- Low-pressure up to 300 psi (2.1 MPa, 21 bar)
- High-pressure up to 2000 psi (14MPa, 140 bar)
- With gun flush box control
- Without gun flush box control
- Color options — 2, 4, 8, 12, 16, 20 & 24

TYPICAL APPLICATIONS

- Line Striping
- Epoxy Coating
- Pipe coatings and Tank linings

TECHNICAL SPECIFICATIONS

Maximum working fluid pressure	3500 psi
Minimum working air pressure	80 psi
Maximum working air inlet pressure.....	130 psi
Maximum fluid temperature.....	200°F (94°C)
Weight	2.5 lb (1.13 kg)
Air inlet size	1/4 NPT quick disconnect nipple
A Component (ISO) inlet size..	-5 JIC; 1/2-20 UNF swivel
B Component (Resin) inlet size-	6 JIC; 9/16-18 UNF swivel
Wetted parts	aluminum, SST, plated carbon steel Carbide, brass, chemically resistant o-rings
Gun dimensions	7.6" X 8" X 3.3"



Shown with heated manifold

ORDERING INFORMATION

	Automatic Spray Guns
2004081	Gun w/ standard static mix
2004082	Gun w/ Hi-Flow static mixer
	<u>Manual Spray Guns</u>
2003759	Gun w/ standard static mixer
2004831	Gun w/ high flow mixer